

Platform

Working Height	68 ft. (20.73 m)
Platform Height	62 ft. (18.89 m)
Horizontal Reach	
w/ Riser Elevated	47 ft. 7 in. (14.5 m)
Riser Height	19 ft. 8 in. (6.0 m)
Platform Capacity	500 lbs. (227 kg)

Dimensions

Platform Size	
Standard	36 x 72 in. (0.91 x 1.83 m)
Optional	36 x 96 in. (0.91 x 2.44 m)
Overall Height (stowed)	8 ft. 11 in. (2.72 m)
Overall Length	30 ft. 7 in. (9.32 m)
Overall Width	8 ft. (2.44 m)
Track	6 ft. 6.5 in. (1.99 m)
Turning Radius	
(outside)	14 ft. 10 in. (4.52 m)
Tailswing	
Riser Up	0
Riser Down	5 ft. 1 in. (1.55 m)
Wheelbase	9 ft. (2.74 m)
Ground Clearance	12 in. (0.30 m)

Performance

Drive/Steer	
AMZ68XT	4 wheel drive, 4 wheel steer
Maximum Drive Speed	
AMZ68XT	3.0 mph (4.8 km/h)
Gradeability (Theoretical)	
AMZ68XT	40%
Tire Size	15x19.5
Tire Fill	Pneumatic
Swing Speed	0.5 rpm

Power Source

Engine	Ford LRG 42.3 water cooled
Engine Horsepower	63 hp (47 kw)
Fuel Tank Capacity	25 gal. (95 L)

Hydraulics

Reservoir Capacity	24 gal. (91 L)
Hydraulic Pump Type	Piston
Filtration	10 micron

Shipping Information

Weight	
AMZ68XT	26,800 lbs. (12157 kg)
Shipping Cube	2,202 cu. ft. (62.35 m ³)

