

Platform

Working Height68 ft. (20.73 m)
Platform Height62 ft. (18.89 m)
Horizontal Reach	
w/ Riser Elevated47 ft. 7 in. (14.5 m)
Riser Height19 ft. 8 in. (6.0 m)
Platform Capacity500 lbs. (227 kg)

Dimensions

Platform Size	
Standard36 x 72 in. (0.91 x 1.83 m)
Optional36 x 96 in. (0.91 x 2.44 m)
Overall Height (stowed)8 ft. 11 in. (2.72 m)
Overall Length30 ft. 7 in. (9.32 m)
Overall Width8 ft. (2.44 m)
Track6 ft. 6.5 in. (1.99 m)
Turning Radius	
(outside)14 ft. 10 in. (4.52 m)
Tailswing	
Riser Up0
Riser Down5 ft. 1 in. (1.55 m)
Wheelbase9 ft. (2.74 m)
Ground Clearance12 in. (0.30 m)

Performance

Drive/Steer	
AMZ68XT4 wheel drive, 4 wheel steer
Maximum Drive Speed	
AMZ68XT3.0 mph (4.8 km/h)
Gradeability (Theoretical)	
AMZ68XT40%
Tire Size15x19.5
Tire FillPneumatic
Swing Speed0.5 rpm

Power Source

EngineFord LRG 42.3 water cooled
Engine Horsepower63 hp (47 kw)
Fuel Tank Capacity25 gal. (95 L)

Hydraulics

Reservoir Capacity24 gal. (91 L)
Hydraulic Pump TypePiston
Filtration10 micron

Shipping Information

Weight	
AMZ68XT26,800 lbs. (12157 kg)
Shipping Cube2,202 cu. ft. (62.35 m ³)

