

## Specifications

### SM4688XT

#### Platform

Working Height	46 ft. (14.02 m)
Platform Height	40 ft. (12.19 m)
Platform Capacity*	1,500 lbs. (680 kg)
Platform Capacity* (w/deck extension)	1,000 lbs. (454 kg)

#### Dimensions

Platform Size	74 x 140 in. (1.88 x 3.56 m)
Roll Out Deck Extension	48 in. (1.22 m)
Overall Height (rails removed)	5 ft. 9 in. (1.75 m)
Overall Length	12 ft. 10 in. (3.91 m)
Overall Width	7 ft. 4 in. (2.24 m)
Wheelbase	7 ft. 8 in. (2.34 m)
Outside Turning Radius	
2 Wheel Steer	23 ft. 2 in. (7.06 m)
4 Wheel Steer	14 ft. 5 in. (4.39 m)
Inside Turning Radius	
2 Wheel Steer	14 ft. 4 in. (4.37 m)
4 Wheel Steer	7 ft. 4 in. (2.23 m)
Ground Clearance	13.4 in. (0.34 m)

#### Performance

Maximum Drive Speed	3.5 mph (5.6 km/h)
Maximum Drive Speed (XT Model)	2.0 mph (3.2 km/h)
Gradeability** (theoretical)	28%
Gradeability** (theoretical) (XT Model)	45%
Lift/Lower Speed	45/50 seconds
Tire Size	12 x 16.5 Loader Lug
Tire Fill	Air

#### Power Source

Engine Make/Model	Kohler M20S
Engine Horsepower	20 hp
Fuel Tank Capacity	13 gal. (49.2 L)

#### Hydraulics

Reservoir Capacity	14 gal. (53 L)
Main Pump	Axial Piston
Steering Pump	Gear

#### Shipping Information

Weight	9,900 lbs. (4491 kg)
Weight (XT Model)	10,000 lbs. (4535 kg)
Shipping Cube	518 cu. ft. (14.5 m <sup>3</sup> )

\*Consult factory on capacities for European and Canadian requirements.

\*\* Published machine gradeability is theoretical. Machine to be in a stowed driving position. Always operate machine on a firm, level surface when elevated.